

Technical Data Sheet:

CMA Stack Kleen

(Commercial Spray Booth Exhaust Stack Cleaner)

Description:

CMA's Stack Kleen is a revolutionary cleaner formulated to make removal of paint residue buildup inside the spray booth exhaust stacks easy. This new nonflammable cleaning formula makes a usually nasty and labor intensive job easier and safer, while being VOC compliant.

Operational Data:

Work area must be well ventilated to conform with OSHA standards. Make sure proper protective equipment is worn according to MSDS. Electrical power must be shut off to the exhaust stack motor and impeller before use.

If product has been stored in a very cold environment, please allow product to warm up to room temperature (65F) and shake before use.

To Apply:

Open the trap doors on the exhaust stack above and below the impeller. Spray on a heavy, saturating coat of Stack Kleen to the paint residue surface. When spraying, it is recommended to use a low pressure pump style sprayer. It is not recommended to use a conventional spray gun since it will atomize the cleaning solution, thus making it ineffective. Stack Kleen is absorbed rapidly and usually within 15 minutes the paint residue surface will begin to lift and fall off. No scraping is necessary. Repeat applications may be necessary depending on the thickness of the paint residue. The dried paint residue can be swept up for safe disposal. Discard in accordance with local, state, and federal laws.

CMA Refinishing Solutions, Inc.
1731 N. Tilghman Street
Philadelphia, PA 19122
215.427.1141
www.cmaproducts.com